

### TECHNICAL DATA

Max. Operating pressure: 350 bar


Rated flow: 480 l/min

Cavity-Tooling: 19A-3 (19AB-3)

Installation torque: 465-500 Nm

Weight: 1.42 (Z=L) kg

Will accept maximum pressure at port (2); suitable for use in cross port relief circuits. If used in cross port relief circuits, consider spool leakage.



### X OPERATION

**30** Standard Type

- Response Time-Typical (10 ms)
- Maximum Leakage Approximately (80 cc/min./70 bar)

### Y SPRINGS ADJUSTMENT RANGES

<b>A</b>	7-210 bar (70 bar Standard Setting)
<b>B</b>	3.5-105 bar (70 bar Standard Setting)
<b>C</b>	10.5-420 bar (70 bar Standard Setting)
<b>D</b>	1.7-55 bar (28 bar Standard Setting)
<b>E</b>	1.7-28 bar (14 bar Standard Setting)
<b>H</b>	2-210 bar (70 bar Standard Setting)
<b>W</b>	10.5-315 bar (70 bar Standard Setting)

### Z OPTIONS

<b>L</b>	Leakproof hex. socket screw.	
<b>K</b>	Handknob with Lock Knob. (Order Code: 6ZAK001)	
<b>C</b>	Stainless Steel Tamper Resistant Cover.	