



| TECHNICAL DATA   |            |
|--|------------|
| Weight:  | 0.24 kg    |
| HEAT INSULATION CLASS H:   |            |
| 356°F  | (180°C)    |
| Ambient temperature range:   |            |
| -22+140°F  | (-30+60°C) |
| Available on request:  |            |
| Different Voltages -<br>Different connectors.  |            |
| Inlet voltage fluctuations must not exceed $\pm 10\%$ of nominal voltage to obtain correct operation and long life of coils. |            |

| X   | Power (W) |
|-----|-----------|
| 260 | 26 Watt.  |
|     |           |
|     |           |
|     |           |
|     |           |
|     |           |

| Y | Connections   |
|---|---|
| H | Connessione A EN 175301-803<br>ISO 4400 (DIN 43650) |
|   |   |
|   |   |
|   |   |
|   |   |

| Z | Voltage (V) |  | Resistance ( $\Omega$ )<br>20~25 °C | Current (A) |          |
|---|-------------|--|-------------------------------------|-------------|----------|
|   | Nominal     |  |                                     | Cold Coil   | Hot Coil |
| B | 110V RAC    | When ordering RAC coils, please make sure also to order <b>ED-30-R-01-A</b> so as to ensure that the solenoid valves can operate properly. | 370 $\pm$ 7%                        | 0.25        | 0.17     |
| A | 220V RAC    |  | 1410 $\pm$ 7%                       | 0.12        | 0.09     |
| E | 12V DC      |  | 5.5 $\pm$ 7%                        | 2.05        | 1.43     |
| D | 24V DC      |  | 21.0 $\pm$ 7%                       | 1.10        | 0.75     |
|   |             |  |                                     |             |          |
|   |             |  |                                     |             |          |
|   |             |  |                                     |             |          |
|   |             |  |                                     |             |          |