



TECHNICAL DATA

Aluminum Body Pressure Rating: 210 bar

Steel Body Pressure Rating: 350 bar

Cavity:

Refer to 11A3

* Refer to Winner Cartridge Valve Catalog.

Aluminum	0.39 kg(WITHOUT VALVES)
Steel	1.13 kg(WITHOUT VALVES)

* If you need the special specification.
Please contact us.

X	PORT SIZE			
	PORTS	PORT	MOUNTING DIMENSIONS	
	1,2	3		
F61M04A	1/2" Code 61 (5000 psi) 4-Bolt Flang Pattern	G 1/4"	Metric	M8 x 1.25-6H
F61E04A	1/2" Code 61 (5000 psi) 4-Bolt Flang Pattern	SAE 6	Inch	5/16"-18 UNC-2B

Y	BODY MATERIAL
A	HIGH-STRENGTH ALUMINUM
T	STEEL (black oxide)

Z	CARTRIDGE VALVES SELECTION
	WITHOUT VALVE
RV0A	RV11A30AL (60LPM, 7-210bar)
CB3H	CB11A33HL (60LPM, 70-280bar)
CO20	CO11A3020N (60LPM, 2.0bar)
CC20	CC11A3020N (60LPM, 2.0bar)
SPOA	SP11A30AL (60LPM, 7-210bar)

Please refer to the list price of cartridge program.