



TECHNICAL DATA

Aluminum Body Pressure Rating: 210 bar

Cavity:

Refer to 16A2

* Refer to Winner Cartridge Valves Catalog.

Aluminum	2.4 kg(WITHOUT VALVES)
----------	------------------------

* If you need the special specification.
 Please contact us.

X	PORT SIZE			
	PORTS	PORT	MOUNTING DIMENSIONS	
	1,2	G		
F61M12G	1-1/2" Code 61 (3000 psi) 4-Bolt Flang Pattern	G 1/4"	Metric	M10 x 1.50-6H (MANIFOLD) M12 x 1.75-6H (FLANGE)
F61E12G	1-1/2" Code 61 (3000 psi) 4-Bolt Flang Pattern	1/4"NPT	Inch	3/8"-16 UNC-2B (MANIFOLD) 1/2"-13 UNC-2B (FLANGE)

Y	BODY MATERIAL
A	HIGH-STRENGTH ALUMINUM
T	STEEL (black oxide)

Z	CARTRIDGE VALVES SELECTION
	WITHOUT VALVE
RPOA	RP16A20AL(380 LPM,7~210 bar)
CV2003	CV16A2003N (320LPM,0.3bar)
FROA	FR16A20AL (0.8-95LPM)
Please refer to the list price of cartridge program.	