



TECHNICAL DATA	
Aluminum Body Pressure Rating:	210 bar
Steel Body Pressure Rating:	350 bar
Cavity: Refer to 19A3 * Refer to Winner Cartridge Valve Catalog.	
Aluminum	2.2 kg(WITHOUT VALVES)
Steel	6.43 kg(WITHOUT VALVES)
* If you need the special specification. Please contact us.	

X	PORT SIZE			
	PORTS	PORT	MOUNTING DIMENSIONS	
	1,2	3		
F61M10A	1-1/4" Code 61 (4000 psi) 4-Bolt Flang Pattern	G 1/4"	Metric	M10 x 1.5-6H
F61E10A	1-1/4" Code 61 (4000 psi) 4-Bolt Flang Pattern	SAE 6	Inch	7/16"-14 UNC-2B

Y	BODY MATERIAL
A	HIGH-STRENGTH ALUMINUM
T	STEEL (black oxide)

Z	CARTRIDGE VALVES SELECTION
	WITHOUT VALVE
RV0A	RV19A30AL (480LPM,7-210bar)
CBCH	CB19A3CHL (3:1,70-280bar)
CO20	CO19A3020N (480LPM,2.0bar)
CC20	CC19A3020N (640LPM,2.0bar)
Please refer to the list price of cartridge program.	