



TECHNICAL DATA

Steel Body Pressure Rating:	350 bar
Rated flow:	400 l/min
Cavity:	Refer to 17A3
* Reference our Cartridge Valves Catalog.	
Steel	12.8 kg (WITHOUT VALVES)
* If you need the special specification. Please contact us.	

X	SELECTION FOR COUNTERBALANCE VALVES
17A3	CAVITY ONLY (WITHOUT VALVE)
CBCH	CB17A3CHL (3:1, 280bar) 2 places.
Please refer to the list price of cartridge program.	

Y	SELECTION FOR CHECK VALVES
17A3	CAVITY ONLY (WITHOUT VALVE)
CC50	CC17A3050N (5.0bar) 2 places.
Please refer to the list price of cartridge program.	

Z	PORT SIZE		MOUNTING DIMENSIONS	
	PORTS VR	PORTS CH, CR		
F62M10	1 1/4" Code 62 (6000 psi) 4-Bolt Flang Pattern	1 1/4" Code 62 (6000 psi) 4-Bolt Flang Pattern	Metric	M10 x 1.50-6H (MANIFOLD) M14 x 2.00-6H (FLANGE)
F62E10	1 1/4" Code 62 (6000 psi) 4-Bolt Flang Pattern	1 1/4" Code 62 (6000 psi) 4-Bolt Flang Pattern	Inch	3/8"-16 UNC-2B (MANIFOLD) 1/2"-13 UNC-2B (FLANGE)